

4x14 AWG 600V Overall Shielded Control Cable

Part Number: **8BCP104xxx**

Applications: Process control industry, Short-range low-frequency signals, Indoor, Outdoor

General Construction: 4 wires are cabled together, overall polyester/aluminum foil shielded and PVC jacketed. The wires are 600 Volts and 105°C rated per MIL-W-16878.

Outer Jacket Material: UV resistant FR-PVC

Outer Diameter: 8.6 mm nom.

Weight: 140 kg/km



Design & Materials

Conductor Material:	Tinned Copper
Conductor Size:	14 AWG
Conductor Construction:	19x0.36 mm
Insulation Material:	FR-PVC -55°C to 105°C rating
Insulation Thickness:	0.4 mm
Insulation O.D.:	2.7 mm nom.
Conductor Color Code:	Color Code:
Overall Shield Design:	100% Coverage
Overall Shield Material:	Aluminum/Polyester Foil
Overall Foil Thickness:	23 µm
Overall Foil Shield:	Yes
Overall Drain-wire Material:	Tinned Copper
Overall Drain-wire size:	18 AWG
Total number of wires:	4
Outer Jacket Thickness:	1.0 mm nom.
Outer Jacket Color:	See TELDOR Jacket Code
Marking:	Per request

Standards

Flamability Rating: IEC 60331-1, UL 1581 VW-1

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Performance

Max. DC Resistance :	10.0 /km@20°C
Dielectric Strength:	2000 V/minute
Min. Bend Radius:	50 mm
Max. Operating Temperature:	+90 °C
Min. Operating Temperature:	-30 °C
UV resistance:	Yes

Prepared By	Revised By	Version Num	Modified on
Dov Shaham	Dov Shaham	1.5	16-06-2008

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.